



**TABLE - I**

**SHUTTER SIZES OF DOOR**

Sl. No.	Location	Shutter Size (in mm )
1.	Entrance Door (1)	1100 x 2045
2.	Entrance Door (2)	1000 x 2045
3.	Room Door (1)	900 x 2045
4.	Room Door (2)	800 x 2045
5.	Kitchen and Store	800 x 2045
6.	Toilet	650 x 2045

**Note :**

1. Masonry opening sizes shall be decided according to the sizes of frames to be used.
2. Doors and windows shutters along with frames shall be fabricated off site.
3. Main entrance door frame shall have double rebates for fixing two sets of shutters viz. normal door shutter and grilled shutter with wire-mesh.
4. The lintel level for all doors shall be at 2100 mm above finished floor level.
5. The materials to be used are left to the choice of the designers. Shutters and frames for doors shall be made of wood or any other suitable alternative materials as prescribed in the specification for the items

**TABLE -II**

**OPENING SIZES OF WINDOW**

Sl. No.	Description	Location	SILL Height	Masonry Opening Size
1.	Window (1)	Habitable Room	750	1800 x 1350
2	Window (2)	Habitable Room	900	1800 x 1200
3	Window (3)	Habitable Room	750	1500 x 1350
4	Window (4)	Habitable Room	900	1500 x 1200
5	Window (5)	Habitable Room	750	1200 x 1350
6	Window (6)	Habitable Room	900	1200 x 1200
7	Window (7)	Habitable Room	750	900 x 1350
8	Window (8)	Habitable Room	900	900 x 1200
9	Window (9)	Habitable Room	750	600 x 1350
10	Window (10)	Habitable Room	900	600 x 1200
11	Window (11)	Habitable Room	750	450 x 1350
12	Window (12)	Habitable Room	900	450 x 1200
13	Window (13)	Kitchen	1050	900 x 1050
14	Window (14)	Toilet	1050	600 x 1050
15	Window (15)	Toilet	1050	450 x 1050

**Notes :**

1. Sill level for windows for habitable rooms shall be at height of 750 mm or 900 mm from the finished floor level.
2. Sill level for kitchen and toilet windows shall be at 1050 mm level.
3. All Windows frames shall have double rebates for fixing two sets of shutters i.e.glass and wire- mesh.
4. Shutters and frames for windows shall be made of wood or any alternative suitable material as prescribed in the specification for the items.